




- Extruded White Acrylic Snap-on Lens
- 20 ga. Cold Rolled Steel Housing
- Painted-after-Fabrication

17N Series

NULITE



Optional - "LKO"
Less End KOs

Project Name:	
Type:	Date:
Catalog #:	

Description:

The Nulite 17N series is a durable petite profile surface mounted lensed luminaire. The white acrylic lens softens lamp brightness. These luminaires are ideal for corridors, walkways, stairwells, utility rooms, lavatories and general purpose areas.

Specifications:

Construction: Housing is die formed of 20 gauge cold rolled steel with 7/8" end KO. All metal parts are finished with white polyester powder coat paint. Smooth white acrylic snap-in lens.

Reflector / Ballast: Ballast cover/reflector is formed and finished with high reflectance white paint. Standard electronic, Class P, ballast. Universal (UNV) voltage ballast is from 120 to 277V.

Lamping: 1 or 2 lamp cross-section T5, 1 lamp cross-section T5HO and T8, in nominal 2', 3' and 4' lengths. Luminaire can be ordered with lamps, consult factory.

Mounting: Surface, individually or continuous rows. Optional AC cable suspended mounting, consult factory.

Labels: UL / cUL listed. Damp location is optional.

Length	Wattage
22-1/2"	14T5, 24T5HO
34-1/4"	21T5, 39T5HO
46-1/8"	28T5, 54T5HO
24-1/8"	17T8
36-1/8"	25T8
48-1/8"	32T8

Ordering Information

Sample: 17N-154T5HO-277-PSN-LKO

Series	Lamp	Wattage	Voltage	Ballast	Options	
17N	1	14T5	UNV	T8 Options	EM ³ Emergency Battery Pack DL Damp Location AL Aluminum Housing SS Stainless Steel Housing (Unfinished) QW Quick Through Wiring for Continuous Row Applications GLR Fusing AC Aircraft Cable Mounting LKO Less End KOs	
		24T5HO ¹	120	IS (Standard) Instant Start		Ballast Factor N Normal (Standard)
	2	21T5	277	PS Program Start		L Low
		39T5HO ¹	347 ²	HEIS High Efficiency Instant Start		H High
		28T5		HEPS High Efficiency Program Start		
		54T5HO ¹	T5/T5HO	Ballast Factor		
		17T8 ¹	PS (Standard) Program Start	N Normal		
		25T8 ¹	HEPS ² High Efficiency Program Start			
		32T8 ¹	All Lamp Dimming Options			
			DIM ² Dimming			
	SD ² Step Dimming					

Notes:

- 1-lamp cross-section only.
- Consult factory.
- Specific voltage must be ordered for this option. Consult factory for nominal 2' and 3' units.

Cover Photography
 Project: **Propeller Offices**
 Photographer: **Will Crocker / Crocker Studio LLC**
 Architect: **CCWIV Architecture**