



Type:	Project:	Qty:
	Date:	
Catalog #:		

Description:

The Nulite GID LED series is a nominal 2'x2' or 4'x4' recessed architectural grid luminaire. This luminaire provides a soft ambient illumination for an aesthetically pleasing, glare-free environment.

Specifications:

Construction: Housing is die formed cold rolled steel. Drop down shielding is die formed of heavy gauge aluminum allowing for easy access to LED compartment. Electrostatically applied powder coat low-gloss white paint finish after fabrication. Optional perforated metal shielding with opal acrylic inlay diffuser.

Reflector / Driver: Reflector is finished with high reflectance white paint. Constant current electronic driver with 0-10V dimming input; dimming range from 100% down to 10%. Universal (UNV) voltage is from 120 - 277V, 50/60 Hz.

LED Module: Distributed LED array in a variety of lumen output packages. LED color is available in (L30) 3000K, (L35) 3500K or (L40) 4000K. Module is replaceable. L70 ≥ 50,000 hours.

Mounting: Grid for Lay-in T-bar ceiling. Non-IC rated.

Labels: ETL listed, conforms to UL Standard 1598 / 8750 and CSA Standard C22.2, Damp location.

Warranty: 5-year limited warranty on LED and Driver.

Ordering Information

Sample: GID-4-80L35-UNV-DIM-PERF

Series	Lumen Package ¹ / LED Color		Voltage	Driver	Options
Grid	(2x2)	L30	UNV	DIM ² Dimming	PERF Perforated Shielding
(2x2)	20 (~2000 lm @ 53W)	L35	120		EM Emergency Battery
GID-2	40 (~4000 lm @ 103W)	L40	277		GLR Fusing
(4x4)	(4x4)				FLEX 6' of Flex
GID-4	40 (~4000 lm @ 103W)				
	80 (~8000 lm @ 206W)				

Notes:

1. Nominal lumen output.
2. 0-10V dimming inputs; dimming range 100% down to 10%, consult factory for specifications.



Specifications and dimensions are subject to change without notification. Specification sheets on our website supersede all other versions. 2015 Rev. E2
Nulite reserves the right to bulk package any order.