



Project Name:	
Type:	Date:
Catalog #:	

Description:

The Nulite INT LED is an ideal solution for lighting cold storage, food processing, parking garages, open exterior structures, commercial and industrial applications. The luminaire housing is NSF certified.

Specifications:

Construction: Rugged corrosion resistant white housing is comprised of fiberglass, continuous closed cell gasket, ribbed acrylic diffuser, toggle latches and end plugs.


Diffuser: Ribbed frosted 85/15 DR acrylic.

Reflector / Driver: Driver cover/reflector is formed of 20 gauge cold rolled steel with a white powder coat finish. Constant current driver with 0-10V dimming input. Universal (UNV) voltage is from 120 - 277V, 50/60 Hz.

LED Module: Distributed LED array in a variety of lumen output packages. LED color is available in (L35) 3500K, (L40) 4000K or (L50) 5000K. Module is replaceable. L70 ≥ 50,000 hours.

Mounting: Pair of stainless steel mounting brackets included.

Labels: ETL listed, conforms to UL Standard 1598 / 8750 and CSA Standard C22.2, Wet location, NSF/ANSI Standard 2, IP67 rated.



Nominal Length	Actual Length
2'	28"
4'	52"
8'	100"

Maximum Ambient Operating Temp. per Lumen Package
Nominal 2' 25 (126° F) 50 (89° F)
Nominal 4' 50 (126° F) 100 (76° F)
Nominal 8' 100 (124° F) 200 (77° F)

Ordering Information

Sample: INT-4-50L40-UNV-DIM-HE

Series	Length	Lumen Package ² / LED Color	Voltage	Driver	Options	
INT						
	2	Nominal 2'	L35	UNV	DIM ³ Dimming	SJT/6 ⁴ 6' SJT Cord OS65 Occupancy Sensor IP65 (Refer to technical page for distribution) CP3/6 ⁴ 6' SJT Cord Plug CP3/6 (NEMA) ⁴ 6' SJT Cord - (NEMA Plug Designation) ie. CP3/6-(L7-20) SSL Optional Stainless Steel Latches HE (1) 1/2" End Hub Entry (Factory Installed)
	4 ¹	25 (~ 2490 lm @ 26.2W)	L40	120		
	8	50 (~ 4979 lm @ 52.3W)	L50	277		
		Nominal 4'				
		50 (~ 4979 lm @ 52.3W)				
		100 (~ 9958 lm @ 104.6W)				
		Nominal 8'				
		100 (~ 9958 lm @ 104.6W)				
		200 (~ 19916lm @ 209.2W)				

Notes:

1. INT-4-50L40... & INT-4-100L400... are DesignLights™ Consortium Qualified, refer to www.designlights.org.
2. Approximate delivered lumens, consult factory for more lumen packages.
3. 0-10V Dimming inputs, consult factory for more information.
4. Luminaire is listed for Damp Location for this option. Consult factory for Wet Location with cord.



Specifications and dimensions are subject to change without notification. Specification sheets on our website supersede all other versions. 2015 Rev. D2 Nulite reserves the right to bulk package any order.

Photometric Curve

Cat. # INT-4-50L40...

Total Lumens - 4979

Total Wattage - 52.3

