



Square Lens Option



Round Lens Option



Type:	Project:	Qty:
	Date:	
Catalog #:		

Description:

The Nulite SA LED series is a specification grade strip utilizing the latest LED technology. This product is ideal for commercial, retail and industrial applications.

Specifications:

Construction: Die formed 20 gauge cold rolled steel housing. Finish is white polyester powder coat paint after fabrication. Consult factory for custom colors. Optional aluminum (painted white) or stainless steel (natural finish) housing.

Lens: Extruded frosted acrylic snap-on lens. Optional extended square or round lens.

Reflector / Driver: Reflector / driver cover is finished with high reflectance white paint. Standard constant current electronic driver with 0-10V dimming input; dimming range from 100% down to 1%. Universal (UNV) voltage is from 120 - 277V, 50/60 Hz. Optional drivers available.

LED Module: Distributed LED array in a variety of lumen output packages. LED color is available in 3000K, 3500K or 4000K and in 80CRI or 90CRI. Module is replaceable. L90 ≥ 100,000 hrs.

Mounting: Surface

Labels: ETL listed, conforms to UL Standard 1598 / 8750 and CSA Standard C22.2. Damp location.

Warranty: 5-year limited warranty on LED and Driver.

Ordering Information

Sample: SA-4-05L35-UNV-D-LKO

Series	Length	Lumen Package / LED Color		Voltage	Driver	Options
SA						
	2 (ft)	03 (~390 lm/ft, 3.28W/ft)	80CRI L30	UNV	Dimming (0-10V)	EM ³ (500) Emergency Battery (500)
	3 (ft)	05 (~568 lm/ft, 4.85W/ft)	L35	120	D ¹ (Dim to 1%)	SQ Square Frosted Lens
	4 (ft)	06 (~724 lm/ft, 6.38W/ft)	L40	277	D0 ² (Dim to 0%)	RD Round Frosted Lens
	8 (ft)	09 (~898 lm/ft, 7.79W/ft)	90CRI H30		Lutron Dimming	LKO Less End KO
		10 (~1036 lm/ft, 9.39W/ft)	H35		See Page 2 for Ordering Codes	AL Aluminum Housing (Painted White)
		Consult Factory for Custom Lumen Package	H40		DALI Dimming	SS Stainless Steel Housing (Natural Finish)
					eldoLED ECOdrive	GLR Fusing
					ELE (Dim to 1%)	QW Quick Through Wiring for Continuous Row Applications
					eldoLED SOLOdrive	OS Occupancy Sensor
					ELS (Dim to 0%)	AC48 Adjustable Aircraft Cable Suspended up to 48" (AC to structure)
						AC120 Adjustable Aircraft Cable Suspended up to 120" (AC to structure)

Notes:

1. Standard driver, don't connect low-voltage wires for non-dimming applications. Consult factory for specifications and manufacturer.
2. Consult factory for specifications and manufacturer.
3. Emergency battery pack not available for 2' and 3' units.

Consult Factory for Custom Colors

Specifications and dimensions are subject to change without notification. Specification sheets on our website supersede all other versions. 2018 Rev.A
Nulite Lighting reserves the right to bulk package any order.

Lutron Driver Ordering Codes

Nulite Code	Lutron Prefix	Lutron Series	Dim Level	Control Type	
				3-Wire	Eco-System™
L11	L3DAE	Hi-lume™	1%		Yes
L12	L3DA3W	Hi-lume™	1%	Yes	
L15	LDE1*	Hi-lume™ - H Series	1%		Yes
L16	LDE5	5-Series	5%		Yes

* Soft-on, Fade-to-Black™

Plan view of 7/8" KOs on back of channel

