



Mounting holes and KOs located on adjacent side.

Project Name:

Type:

Date:

Catalog #:

Description:

The Nulite CL series luminaire is designed to be corner mounted which is ideal for illuminating corridors and room perimeters. The luminaire is available in a rough service housing for vandal resistant or hard use applications.

Specifications:

Construction: Die formed 20 gauge cold rolled steel housing with T-hinge door frame, latches and frosted acrylic lens. Other shielding options are available, consult factory. Housing finish is white electrostatically applied powder coat paint.

Optional Vandal Resistant Housing (VR) - Die formed 16 gauge cold rolled steel housing with piano hinge door frame and spanner head stainless steel door screws. Housing finish is white electrostatically applied powder coat paint.

Reflector / Driver: Reflector / driver cover is finished with high reflectance white paint. Standard constant current electronic driver with 0-10V dimming input; dimming range from 100% down to 1%. Universal (UNV) voltage is from 120 - 277V, 50/60 Hz. Optional drivers available.

LED Module: Distributed LED array in a variety of lumen output packages. LED color is available in 3000K, 3500K, 4000K or 5000K in 80CRI. Module is replaceable. L90 ≥ 100,000 hrs.

Mounting: Wall.

Labels: ETL listed, conforms to UL Standard 1598 / 8750 and CSA Standard C22.2. Damp location.

Warranty: 5-year limited warranty on LED and Driver.

Ordering Information

Sample: CL-4-10L35-UNV-D-EM

Series	Length	Lumen Package/LED Color		Voltage	Driver	Options
CL						
	4 (ft)	07 (~728 lm/ft, 6.38W/ft)	80CRI	UNV	Dimming (0-10V)	VR Vandal Resistant Housing (Refer to description above)
	8 ¹ (ft)	10 (~1036 lm/ft, 9.39W/ft)	L30	120	D ² (Dim to 1%)	EM Emergency Battery Pack
		14 (~1489 lm/ft, 17.3W/ft)	L35	277	D0 ³ (Dim to 0%)	AL Aluminum Housing (0.060")
		Consult Factory for Custom Lumen Package	L40		Lutron Dimming	PH Piano Hinge
			L50		See Page 2 for Ordering Codes	SS Stainless Steel Housing (Unfinished)
					DALI Dimming	QW Quick Through Wiring for Continuous Row Applications
					eldoLED ECOdrive ELE (Dim to 1%)	GLR Fusing
					eldoLED SOLOdrive ELS (Dim to 0%)	16GW 16 Gauge CRS Housing w/ Piano Hinge

Notes:

1. Nominal 8' housing has two doors.
2. Standard driver, don't connect low-voltage wires for non-dimming applications. Consult factory for specifications and manufacturer.
3. Consult factory for specifications and manufacturer.



Specifications and dimensions are subject to change without notification. Specification sheets on our website supersede all other versions. 2017 Rev. A
Nulite Lighting 10770 East 51st Avenue, Denver, CO 80239 Phone 303-287-9646 Fax 303-287-0316 www.nulite-lighting.com

Photometric Curve

Cat. # CL-4-14L35....
 Efficacy - 85.8 lm/W
 Total Lumens - 5955
 Total Watts - 69.4

