



Project Name:	
Type:	Date:
Catalog #:	

Description:

The Nulite G series is a commercial grade recessed grid lay-in troffer. Unit has a concealed latch hinge door with standard A12 prismatic lens.

Specifications:

Construction: Die formed housing of 23 gauge cold rolled steel with embosses for maximum rigidity. Housing is finished with white enamel paint. Snap-in access plate for easy wiring without opening luminaire.

Reflector / Ballast: Ballast cover/pan is finished with high reflectance white enamel paint. Standard electronic, Class P, ballast. Universal (UNV) voltage is from 120 to 277V.

Shielding: Latch hinge door is standard with A12 prismatic lens. Optional - A15 pattern, smooth white lens or clear acrylic.

Lamping: 1, 2, 3 or 4 lamp cross-section of T5, T5HO or T8. Luminaire can be ordered with lamps, consult factory.


Mounting: Exposed T-bar ceiling, Non-IC rated.

Labels: UL / cUL listed. Non-IC rated. Damp location is optional.


(2-Lamp)




(2-Lamp)




(1 or 3-Lamp)



(3-Lamp)



(4-Lamp)



Ordering Information

Sample: G2-332T8-277-HEISH-EM

Series	Lamp	Wattage	Voltage	Ballast		Options
(1x2 or 1x4) G1 ¹	(1x2 or 1x4) 1 ²	(1x2 or 2x2) 14T5	UNV 120	T8 Options	Ballast Factor	EM ⁴ Emergency Battery Pack
	2	24T5HO		IS (Standard) Instant Start	N Normal (Standard)	DL Damp Location
	3 ²	17T8	277	PS Program Start	L Low	A15 A15 Pattern Lens
	(2x2 or 2x4) 2	(1x4 or 2x4) 28T5	347 ³	HEIS High Efficiency Instant Start	H High	CL Clear Acrylic Lens
(2x2 or 2x4) G2	3	54T5HO		HEPS High Efficiency Program Start		ASW Acrylic Smooth White Lens
	4	32T8		T5/T5HO	Ballast Factor	GLR Fusing
				PS (Standard) Program Start	N Normal	FLEX3 6' of Flex, 3-wire
				HEPS ³ High Efficiency Program Start		FLEX4 6' of Flex, 4-wire (Consult factory - requires dual circuits)
				All Lamp Dimming Options		
				DIM ³ Dimming		
				SD ³ Step Dimming		

Notes:

1. EM or MLS is not available for the 1 or 3 lamp G1 Series.
2. Not available for T5 or T5HO.
3. Consult factory.
4. Specific voltage must be ordered for this option. Consult factory for nominal 2' units.

Specifications and dimensions are subject to change without notification. Specification sheets on our website supersede all other versions. 2015 Rev. D1
Nulite reserves the right to bulk package any order.

Photometric Curve

Cat.# G2-432T8...

Initial lamp lumens - 11600 (4 lamps)

