

Available in



Regolo 4 Trimless Series

Type:	Project:	Qty:
	Date:	
Catalog #:		

Description:

The Nulite Regolo RT4 series is a nominal 4" wide recessed trimless luminaire. The product is ideal for illuminating corridors, open and private offices, classrooms, lobbies and general purpose rooms.

Specifications:

Construction: The housing consists of extruded aluminum side rails with formed cold rolled steel back channel and heavy gauge end caps. Standard finish is powder coat textured white. Optional silver, black or custom color paint finishes.



Reflector / Ballast: Reflector / ballast cover is finished with high reflectance white paint. Standard electronic, Class P, ballast. Universal (UNV) voltage ballast is from 120 - 277V.

Shielding: Extruded frosted acrylic or satin white acrylic snap-in lens with DR or semi-specular cross blade flush baffle only available in nominal 6" high housing (Consult Factory).

Lamping: 1 or 2 lamp cross-section T5, T5HO or T8. Luminaire can be ordered with lamps, consult factory.

Mounting: Recessed, individual or continuous row.

Labels: UL / cUL listed, Non-IC rated, Damp location.



5/8" Drop Lens Option

Ordering Information

Sample: RT4-2T5-N-UNV-PSN-1C-FRF-WH-20'

Series	Lamp	Staggered	Voltage	Ballast		Circuit	Shielding	Color	Length	Options	
RT4											
RT4 (Trimless - Nom. 4")	1T5	N (Non-staggered)	UNV	T8 Options		1C Single Circuit	FRF (Frosted Flush)	WH (White - Standard)	2'	GLR Fusing FLEX 6' of Flex OS ⁵ Occupancy Sensor at end of run / unit DS ^{5,6} Daylight Sensor at end of run / unit	
	1T5HO		120	IS (Standard)	N Normal (Standard)	1E Single Circuit w/ EM Circuit	FRD (Frosted Drop Opaque End)	BK (Black)	3'		
	1T8		277	PS	L Low	1B ³ Single Circuit w/ Battery Pack	FRL (Frosted Drop Luminous End)	SV (Silver)	4'		
	2T5		347 ¹	HEIS	H High	2C ² Dual Circuit	STF (Satin White Flush)	CC (Custom Color)	5'		
	2T5HO			T5 / T5HO		2E ² Dual Circuit w/ EM Circuit	STD (Satin White Drop Opaque End)		6'		
	2T8			PS (Standard)	N Normal	2B ^{2,3} Dual Circuit w/ Battery Pack	STL (Satin White Drop Luminous End)		7'		
					All Lamp Dimming Options				8'		Continuous Runs XX' Specify run length in 1 foot increments. Consult factory for custom lengths.
					DIM ¹ Dimming						
					SD ¹ Step Dimming						
					IS=Instant Start PS=Program Start HEIS=High Efficiency Instant Start HEPS=High Efficiency Program Start						

Notes:

- Consult factory.
- Not available in all options, consult factory.
- Specific voltage must be ordered for this option. Reduced profile battery packs only, consult factory for specifications.
- Only available in nominal 6" high housing, consult factory.
- Luminaire will have a 3" extension for the sensor.
- Not available with luminous end drop lens.

Specifications and dimensions are subject to change without notification. Specification sheets on our website supersede all other versions. 2017 Rev. D2 Nulite reserves the right to bulk package any order.

Shielding Options




Frosted Lens

This diffuser is designed for a balance between efficiency and lens uniformity. (Transmission ~ 89%)

Satin White Lens

This diffuser is designed for visible lens uniformity. It's recommended for regressed lens configuration in our shallow housing. (Transmission ~ 69%)

Sensor Options




Occupancy or Daylight Sensor in a nominal 3" long insert plate. A 3" extension is needed for 4" high products. Lamps extend under the sensor plate and are removable without removing the sensor for 6" high products.

Drop Lens - "L"



5/8" Drop Lens with Luminous Acrylic Ends

Drop Lens - "D"




5/8" Drop Lens with Opaque White Metal Ends


Semi-Specular Baffle



Back of Housing Mounting Holes & Power Feed KO



Individual Lengths




Non-Staggered Run Length (A = Stand Alone Housing, S = Starter Housing, M = Mid Housing, E = End Housing)

	2'	3'	4'	5'	6'	7'	8'	9'	10'	11'	12'	13'	14'	15'	16'	17'	18'	19'	20'	21'	22'	23'	24'	25'	26'	27'	28'	29'	30'	31'	32'	33'	34'	35'	36'	37'	38'	39'	40'							
24A	1																																													
36A		1																																												
48A			1																																											
60A				1																																										
72A					1																																									
84A						1																																								
96A							1																																							
72S								1	1							1	1							1	1								1	1												
96S										1	1	1	1	1	1	1			1	1	1	1	1			1	1	1	1	1	1			1	1	1	1	1	1	1	1	1	1	1	1	
96M																1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	3	3	3	3	3	3	3	3	3	3	3	3	3	3	
36E							1	1								1	1						1	1							1	1														
48E								1	1								1	1							1	1						1	1													
60E											1									1								1											1							
72E												1									1									1																
84E													1									1									1															
96E															1								1																							


Specifications and dimensions are subject to change without notification.

Photometric Curves


Cat. # RT4-1T8-N...-FRF-...-4'
 Frosted Flush Lens
 Initial lamp lumens - 2800



Cat. # RT4-1T8-N...-STF-...-4'
 Satin White Flush Lens
 Initial lamp lumens - 2800



Cat. # RT4-2T5-N...-FRF-...-4'
 Frosted Flush Lens
 Initial lamp lumens - 5200



Specifications and dimensions are subject to change without notification.