



Project Name:	
Type:	Date:
Catalog #:	

Description:

The Porta Sottile series is a fully luminous architectural recessed luminaire. This cost effective, energy efficient luminaire series provides soft ambient illumination and features a tool-less captive latch-hinge door frame assembly for quick access of lamp compartment.

Specifications:

Construction: Die formed cold rolled steel housing with white enamel finish. Optional die formed 20 gauge cold rolled steel housing and powder coated white paint after fabrication. Access plate allows for easy wiring without opening luminaire.

Shielding: Extruded 3-piece interlocking, impact resistant, UV stabilized virgin frosted acrylic diffuser for visual comfort. Optional center diffusers: frosted linear, round perf overlay, clear linear w/ internal radial baffle. Die formed cold rolled steel door frame. Tool-less, over-lapping, captive latch-hinge door frame assembly allows for quick maintenance from below.

Reflector / Ballast: Ballast cover/pan is finished with high reflectance white paint. Standard electronic, Class P, ballast. Universal (UNV) voltage is from 120 - 277V.

Lamping: 1, 2 or 3 lamp cross-section. Luminaire can be ordered with lamps, consult factory.

Mounting: Non-IC rated. Acoustical grid or optional flange kit for inaccessible ceiling types.

Labels: UL / cUL listed. Optional Damp location.

Ordering Information

Sample: P2D-228T5-277-PSN-EM

Series	Lamp	Wattage	Voltage	Ballast	Options
P2D					
(Nom. 2' width)	1 2 3 ¹	(2' Nom. Length) 14T5 24T5HO 17T8 40FT 50FT 55FT (4' Nom. Length) 28T5 54T5HO 32T8	UNV 120 277 347 ²	T8 Options IS (Standard) Instant Start PS Program Start HEIS High Efficiency Instant Start HEPS High Efficiency Program Start T5/T5HO/FT PS (Standard) Program Start HEPS ³ High Efficiency Program Start All Lamp Dimming Options DIM ³ Dimming SD ³ Step Dimming	Ballast Factor N Normal (Standard) L Low H High Ballast Factor N Normal DL Damp Location FLG Flange Kit CP Chicago Plenum SIC Seismic Clips 20PAF 20 ga. CRS / Paint After Fabrication DSR Daylight Sensor - Remote FLEX3 6' of Flex, 3-wire FLEX4 6' of Flex, 4-wire
					IRB Internal Radial White Baffle with Clear Linear Prism Center Diffuser RFD Frosted Linear Prism Center Diffuser RPO Round Perforated Overlay Center Diffuser MLS Multi-Level Switching (3-Lamp Only) EM ⁴ Emergency Battery Pack GLR Fusing DL Damp Location FLG Flange Kit CP Chicago Plenum SIC Seismic Clips 20PAF 20 ga. CRS / Paint After Fabrication DSR Daylight Sensor - Remote FLEX3 6' of Flex, 3-wire FLEX4 6' of Flex, 4-wire

Notes:

1. Not available for Long Twin Tube. Consult factory for T5HO.
2. Not available with EM option.
3. Consult factory.
4. Specific voltage must be ordered for this option. Some EM's may require "doghouse" or remote mounting, consult factory.